

ColorSave® - 1000 Feeder

The only gravimetric feeder that offers Smart-Clean automatic quick cleaning

Features

- Stores up to 500 recipes, shorter setup time
- Easy replacement of feeding screw
- Easy cleaning when switching colors and materials
- Optional integrated Venturi vacuum loader
- Real-time data collection and management of material consumption



Features

- Purge colorant in just 10 seconds
- Simply press the "Empty" button and remaining colorant or masterbatch returns to the storage chamber
- No more manual clean-outs between jobs
- Enhance employee safety and reduce change over time



ColorSave® - 1000 Feeder

Specifications

Hopper	3/5/10 liter
Output Range	0.2-100 kg/h
Motor	Powerful step motor
Display	4.3" color touch screen
Recipes	1000
Load cell	15 kg for 3 or 5 liter volume 30kg for 10 liter volume
Alarm Output	N/O or N/C dry contact 0V
Weight	3 liter: 16 kg, 5 liter: 18 kg, 10 liter: 34 kg
Power	100-240v, 200W, 50/60hz



Multiple Applications

- Injection Molding
- Extrusion
- Extrusion Blow Molding



A dosing system able to regulate two feeders connected to the same neckpiece with a single control unit


Features

- Unparalleled accuracy and precision
- Easy and intuitive control unit
- Unmatched cost-savings
- Improved quality of final product
- Vastly reduces the amount of rejects
- Stores up to 500 recipes, shortening setup time
- Easy replacement of feeding screw
- Ability to combine gravimetric and volumetric channels
- Compensation of masterbatch amount when using scrap material




Specifications

Hopper Volume	3/5/10 liter with gravimetric channel 6/12/20 liter with volumetric channel
Output Range	0.2-100 kg/h with gravimetric channel 0.02-200 kg/h with volumetric channels
Motor	Powerful step motor
Display	7" color touch screen



The World's First Small Dose Gravimetric Feeder

Designed specifically for small products



Specifications

Hopper	640cc
Output Range	Up to 80 g/minute
Dosing Technique	Vibration System
Communication	Modbus TCP/IP
Weight Resolution	0.01g
Loader	Optional integrated
Mounting & Feeding	Venturi loader Via neckpiece adapter
Alarm Output	N/O or N/C dry contact 0v
Power	100-240V, 50/60 Hz, 20 V/A

Features

- **Small Dose Accuracy**
 - ColorSave-Micro uses a single vibrating channel to accurately and consistently deliver the correct dose.
- **Easy Calibration & Less Maintenance**
 - The single channel is used for nearly all additives, handles wide range of feed rates and cleans easy.
- **Nearly all types of additives**
 - ColorSave-Micro supports pellets, several types of regrinds and powders, and Micro-granules

